

item	Metric size	Qty	NPT size	Qty
501/421 (Nickel Plated Brass, for Non-Armoured Cable)	2K/M16	73	OS 1/2"NPT (New)	45
	OS/M20	42	O 1/2"NPT (New)	53
	O/M20	11	A 1/2"NPT (New)	163
	A/M20	195	A 3/4"NPT (New)	77
	B/M25 (New)	53	B 3/4"NPT (New)	31
	C/M32	34	B 1"NPT	69
	C2/M40	36	C 1"NPT (New)	12
	D/M50 (New)	19	C 1.1/4"NPT	58
	E/M63	7	C2 1.1/4"NPT	26
	F/M75	5		
501/453/RAC (Nickel Plated Brass, for Armoured Cable)	O/M16	60	OS 1/2"NPT (New)	129
	OS/M20	406	O 1/2"NPT	354
	O/M20 (New)	153	A 1/2"NPT	409
	A/M20 (New)	168	A 3/4"NPT (New)	240
	B/M25	863	B 3/4"NPT	114
	C/M32	643	B 1"NPT	125
	C2/M40	226	C 1"NPT	110
	D/M50	86	C 1.1/4"NPT	92
	E/M63	4	C2 1.1/4"NPT	66
	F/M75	8	C2 1.1/2"NPT	66
			D 1.1/2"NPT	20
		D 2"NPT	23	
501/453/UNIV (Nickel Plated Brass, for Armoured cable, coldflow character)	Os/M20 (New)	55	OS 1/2"NPT	9
	O/M20	239	O 1/2"NPT	6
	A/M20 (New)	178	A 1/2"NPT (New)	79
	B/M25	949	A 3/4"NPT (New)	58
	C/M32	291	B 3/4"NPT (New)	26
	C2/M40	4	B 1"NPT	11
	D/M50	13	C 1"NPT (New)	20
	E/M63		C 1.1/4"NPT (New)	20
487(475) (Nickel Plated Brass, Plug)	487/ M16	16	475/ 1/2"NPT	57
	487/ M20	153	475/ 3/4"NPT	263
	487/ M25	86	475/ 1"NPT	220
	487/ M32	34		
	487/ M40	9	390(Hexa Head)/ M16	33
	487/ M50	4	390(Hexa Head)/ M20	2
	487/ M63		494/M25	5
476 (Nickel Plated Brass, adaptor)	M16(M)-M20(F)	3	1/2"(M)-M20(F)	43
	M20(M)-M25(F)	158	3/4"(M)-M20(F)	20
	M25(M)-M20(F)	40	3/4"(M)-M25(F)	104
	M25(M)-M32(F)	71	1"(M)-M25(F)	73
	M32(M)-M25(F)	22	1"(M)-M32(F)	77
	M20(M)-1/2"(F)	30	1/2"(M)-3/4"(F)	82
	M20(M)-3/4"(F)	76	3/4"(M)-1/2"(F)	34
	M25(M)-3/4"(F)	62	3/4"(M)-1"(F)	37
	M25(M)-1"(F)	51	1"(M)-3/4"(F)	113